



**PONTON**  
WE ARE THE 2 IN B2B

# X/P Messenger 3.11 Migration Guide

---

Version: 3

Date: 30-Mar-2021

## Copyright Notice



This document is the confidential and proprietary information of PONTON GmbH ("Confidential Information"). You shall not disclose such Confidential Information and shall use it only in accordance with the terms of the license agreement you entered into with PONTON GmbH.

# Table of Contents

<b>1. Preparation .....</b>	<b>3</b>
<b>2. Windows .....</b>	<b>4</b>
<b>3. Linux .....</b>	<b>5</b>
<b>4. Messenger Private Agreement .....</b>	<b>6</b>
<b>5. Messenger Partner Folder .....</b>	<b>7</b>
<b>6. Messenger Config Folder .....</b>	<b>8</b>
<b>7. Database Driver .....</b>	<b>9</b>
<b>8. Archive and Archive_Failed.....</b>	<b>11</b>
<b>9. Config Patch Installation (optional).....</b>	<b>12</b>
<b>10. Finalize.....</b>	<b>13</b>

# 1. Preparation

1. Stop the old messenger instance.

## 2. Windows

1. Uninstall the messenger Windows Service with the `uninstallService.bat` script.
2. Unpack `PontonXP-3.11.0-Windows.zip` in a new folder.
3. Adjust the windows service configuration file based on the old installation:  
Take the following values from the old installation (see `\ServiceInstaller\wrapper.conf` or `\launcher\conf\wrapper.conf`):

```
# Maximum Java Heap Size (in MB)
wrapper.java.maxmemory=512
# Name of the service
wrapper.ntservice.name=pontonxpmessenger
# Display name of the service
wrapper.ntservice.displayname=Ponton X/P Messenger
```

and put them to the new installation (see `\launcher\conf\wrapper.conf`):

```
# Ponton X/P Display Name.
set.MESSENGER_NAME="set value in wrapper.conf"
# Maximum Java Heap Size (in MB)
set.MAX_MEMORY=512
# Name of the service
set.NTSERVICE_NAME=pontonxpmessenger
# Display name of the service
set.NTSERVICE_DISPLAYNAME=Ponton X/P Messenger
```

4. Finally install the Windows Service using the „`installService.bat`“ script.

## 3. Linux

1. Unpack PontonXP-3.11.0-Linux.zip in a new folder.
2. Check that the script file 'pontonxp' is executable. If it is not executable change the permissions with "chmod 755 pontonxp".
3. The script file 'pontonxp' needs to be adjusted when the standard autostart mechanism of the operation system is used. There are comments for these parameters in the script file.

## 4. Messenger Private Agreement

If the file `privateagreement.vm` exists in the old installation (see `\xmlpipe\config\partneragreement\private\privateagreement.vm`) copy it to the new installation (see `\config\partneragreement\private\`).

## 5. Messenger Partner Folder

The partner folder of the old installation (see `\xmlpipe\config\partnerprofiles\`) has to be copied to the new installation (see `\config\partnerprofiles\`).

## 6. Messenger Config Folder

The configuration following files of the old installation (see \xmlpipe\config\) has to be copied to the new installation (see \config\):

- hotfolder.xml
- messenger.xml
- server.xml
- keystore
- tomcat-users.xml

Adjust the server.xml by changing the two keystore paths at the SSL block to:

```
<SSL>
  <Keystore>$XP_CONFIG_FOLDER/keystore-ssl</Keystore>
  ...
  <ClientAuthKeystore>$XP_CONFIG_FOLDER/keystore-ssl</ClientAuthKeystore>
  ...
</SSL>
```



## 7. Database Driver

Due to the upgrade to JAVA 15, the latest database drivers must be used.

Copy the database driver to the folder \lib\_ext\.

Depending on the used database the messenger.xml must be updated with right values. In the following marks "SERVER" and "DBNAME" must be replaced the values of the old installation.

**MSSQL:** JDBC driver 9.2.1 (mssql-jdbc-9.2.1.jre15.jar) <https://go.microsoft.com/fwlink/?linkid=2155948>

### Code Block 1 messenger.xml

```
<Database>
  <Dialect>SQLServer2012</Dialect>
  <DriverClass>com.microsoft.sqlserver.jdbc.SQLServerDriver</DriverClass>

  <URL>jdbc:sqlserver://SERVER:1433;database=DBNAME;encrypt=true;trustServerCertificate=true</URL>
  ...
</Database>
```

**Oracle:** JDBC driver 21.1 (ojdbc11.jar) <https://www.oracle.com/database/technologies/appdev/jdbc-ucp-21-1-c-downloads.html>

### Code Block 2 messenger.xml

```
<Database>
  <Dialect>Oracle12c</Dialect>
  <DriverClass>oracle.jdbc.driver.OracleDriver</DriverClass>
  <URL>jdbc:oracle:thin:@SERVER:1521:DBNAME</URL>
  ...
</Database>
```

**MySQL:** JDBC driver 8.0.23 (mysql-connector-java-8.0.23.jar) <https://dev.mysql.com/downloads/connector/j/8.0.html>

**Code Block 3 messenger.xml**

```
<Database>
  <Dialect>MySQL55</Dialect>
  <DriverClass>com.mysql.cj.jdbc.Driver</DriverClass>

  <URL>jdbc:mysql://SERVER:3306/DBNAME?autoReconnect=true&useSSL=true&allowPublicKeyRetrieval=true</URL>
  ...
</Database>
```

## 8. Archive and Archive\_Failed

By default the message archive is stored in the folder „\xmlpipe\archive“ and “\xmlpipe\archive\_failed”.

If these default paths are used, then these folders need to be moved (or copied) to the new installation “\data” (e.g \data\archive), otherwise the used archive paths need to be set using the Messenger GUI.

## 9. Config Patch Installation (optional)

After preparation of the new installation, copy the needed config patch (patch.jar) to the folder \update\ and all needed configuration files to the config folder. Then start the messenger to install the patch.

## 10. Finalize

On the Windows machine use Windows Services dialog to start or stop the messenger.

On the Unix systems use the script file 'pontonxp' to start or stop the messenger.

Verify in the log file /data/log/wrapper.log that the startup was successful. You should see a message:

### Code Block 4 wrapper.log

```
Ponton X/P Messenger V3.11.0 (Build 202103261430) is initialized.
```

PONTON GmbH  
Dorotheenstraße 64  
GERMANY 22301 Hamburg  
Web: <http://www.ponton.de>